POLY FORM

Mould Release Agent

Product Description

POLY FORM is a blend of chemical release agent & mineral oils specially formulated to give an easy release of formwork and high quality surface finish to concrete.

Typical Application

POLY FORM is suitable for application to timber, plywood, steel, plastic formwork and moulds before casting concrete, to ensure high quality stain free concrete surface.

Product Features

- Very economic coverage rates can be obtained without difficulty.
- Ready to use; quickly & easily applied with brush, roller, spray or cloth.
- Protects steel forms from rusting.
- Reduces the incidence of blowholes, surface blemishes and staining.
- Provides quick positive release of formwork, reducing lab our costs for cleaning & damage of formwork.
- Suitable for use on all types of formwork.
- Forms are easily & smoothly released from cured concrete.

Properties

Appearance Clear amber liquid. Specific Gravity 0.83 At 20°C. Chloride Content Nil. Flash Point Above 60° C.

Guide For Application

Surface Preparation

All forms must be cleaned from any adherent

Material, concrete, cements latency or previous oil deposits.

Coating

Apply a thin coat of **POLY FORM** uniformly by spray, roller or brush.

Over coating may lead to surface dusting and is uneconomical.

Cleaning

Spillage of **POLY FORM** can be removed with soap and water.

Packaging

POLY FORM is supplied in 220 lit. drums.

Coverage

Depends on porosity of mould or formwork surface; a coverage of $20 - 40 \text{ m}^2$ per lit. for wooden formworks and 60 m2 per lit. for steel moulds.

Storage

POLY FORM should be stored in shaded areas.

Shelf Live

One year when stored as recommended.

Health and safety

- Any splashes on skin should be washed with soap and water.
- Seek medical assistance in case of contact with eyes, after washing it with running water.

<u>Guarantee / Warranty</u>

We warrant our products to be of good quality and manufactured to rigid standards. This warranty is in lieu of any and all other warranties expressed or implied.

This data sheet is published for information only. It is believed to be correct but no liability is accepted for it or the suitability of the product for any particular purpose.

POLYCOO services are free and the company dose not accepts liability for any loss arising from it.

Technical Services

For any further technical advice and recommendation for the use of all **POLYCOO** products, please consult the nearest **POLYCOO** technical office.





Under technical collaboration with

Polycoo Industries Ltd.

Sole distributor in Egypt: Polycoo Company www.polycoo.com 5 Kamel Sedki Street, Ramsis Square, Cairo, Egypt Sales Tel.: ++202-5918653/++2025918053/++20-122-3102700 Fax: ++202-5918053