

POLY ROYALE COAT

Luxury Acrylic Paints

INSTRUCTIONS FOR USE

1) Surface preparation:

- Surface must be clean, free from oil, grease, dirt and chalk... etc.
- Old painted surfaces should be cleaned from loose paint and other materials that can affect adhesion

2) Recommended Application System:

- Use **POLY SEAL PRIMER** as a primer coat before applying putty. Additional coat after applying putty helps improving adhesion and spreading rate.
- Use **POLY ACRY PUTTY / POLY UNOSHIELD PUTTY** for smoothening and leveling the surface
- Mix **POLY ROYALE COAT** thoroughly to uniform consistency before use.
- It is recommended to dilute with water not exceeding 10% for ease of application depending on climatic condition.
- Allow 6 hours of drying between each coat.

REMARKS

Alternative systems may be specified, depending on area of use.
Please refer to technical office for application advice

APPLICATION TOOLS

Roller, Brush, Spray Gun.

THEORETICAL COVERAGE

10-13.5 m² / Ltr. per coat at 30 - 40 microns DFT. Practical coverage varies depending on surface porosity, application method, DFT and losses.

PACKAGING

Refer to company price list or contact the local representative

STORAGE & SHELF-LIFE

36 months in original tightly closed containers away from direct sunlight and excessive heat.

'Teflon is a registered trademark of The Chemours Company FC, LLC

used under sublicense by Soib Chemical S. A. E "For exterior use please refer to the exterior colour chart.

'Refer to Material Safety Data Sheet (MSDS) before using the product.

Our Recommendations are based on extensive research as well as practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice. Please note that this data sheet supersedes any previous prints. For any additional information, please consult our technical office .May/2015



Under technical collaboration with

Polycoo Industries Ltd.

Sole distributor in Egypt: Polycoo Company

www.polycoo.com

5 Kame lSedki Street, Ramsis Square, Cairo, Egypt

Sales Tel.: ++202-5918653/++2025918053/++20-122-3102700 Fax: ++202-5918053