

POLY DECORA COAT

INTERIOR / EXTERIOR PAINT

DESCRIPTION & USES

- **POLY DECORA COAT Synthetic Matt** is a matt alkyd resin-based paint in solvent base, containing highly selected pigments and additives.
- For Exterior and Interior use.
- Can be applied over: wood, soft and hard board, concrete, plaster, zinc, metallized steel, new iron and galvanized steel (after special treatment).
- Good Hiding Fewer, wash ability and weather resistance.
- Can be used to make lacquer putty by adding DECORA Synthetic Matt to Lithopone (Zinc) & Calcium Carbonate.

PROPERTIES

Finish	Matt
Color	White
Density at 25°C	1.46 - 1.54 kg/ (white)
Viscosity at 25°C	115 - 120 KU (white)
% Solid Content by volume	43 ± 2
Wash ability / Wet Scrubbing	Highly washable
Diluents / Thinner	White Spirit
Drying Time at 25°C	Touch Dry: 30 - 60 min.
and relative humidity 50%	Recoat: 3-4 hours
Recommended DFT	Hard Dry: 24 hours
	30 - 40 /urn

INSTRUCTIONS FOR USE

1) Surface preparation:

- Surface must be clean, free from oil, grease, dirt, chalk...etc.
- Surface must be dry, clean and free from oil, grease, dirt, chalk...etc.
- On ferrous and non-ferrous metals use suitable primer like RUSTPROOF 111 before applying DECORA Synthetic Matt.
- On painted substrates; wash and leave to dry, make sure that old paints are not loose before new painting.

2) Application:

- In case of using brush or roller
First Coat: dilute with 15% White Spirit.
Second Coat: dilute with 5 -10% White Spirit.
- In case of using spray-gun:
Dilute with 10 - 20% White Spirit depending on gun.

APPLICATION TOOLS

Brush - Roller - Airless Spray Gun

COVERAGE

12.5 -16.5 m²/l per coat at the recommended DFT in case of white according to preparation & porosity of substrate.

PACKAGING

Available in small containers and gallons. Refer to company price list for more information.

STORAGE & SHELF-LIFE

18 months in original tightly closed containers away from direct sunlight and excessive heat.

Our recommendations are based on extensive research as well as practical experience. Results can not be guaranteed where the actual application work is beyond our control. Customers must carry out their own investigations and test the suitability of our materials before use for their intended purposes. Please note that this data sheet supersedes any previous prints. For any additional information, please consult our customer service department.



Under technical collaboration with

Polycoo Industries Ltd.

Sole distributor in Egypt: Polycoo Company

www.polycoo.com

5 Kamel Sedki Street, Ramsis Square, Cairo, Egypt

Sales Tel.: ++202-5918653/++2025918053/++20-122-3102700 Fax: ++202-5918053