

POLY TILE MORTAR

Cementations Tile Adhesive

PRODUCT DESCRIPTION

POLY TILE MORTAR is a blend of selected ordinary Portland cement, graded sand & organic polymer. It is especially formulated for fixing wall and floor tiles.

TYPICAL APPLICATIONS

- For fixing swimming pool tiles.
- For fixing wall and floor tiles.
- For decorative stone cladding.

PRODUCT FEATURES

- High water resistance.
- Easy to use.
- Thin and thick bed.

STANDARDS

POLY TILE MORTAR complies with the following standards BS 5980 Type 1 & BS 5385 Append A.

PROPERTIES

colour

Gray or white.

Compressive Strength

45 N/mm².

Adhesion

Excellent to tiles and decorative stone.

Tensile Strength

6 N/mm²

Water Absorption

<5%.

GUIDE FOR APPLICATION

Preparation

Surface to be tiled should be sound, clean, free from any dust.

Remove all loose particles, oil, grease and curing compounds. Surfaces treated should be washed with clean water.

MIXING

POLY TILE MORTAR by adding the powder to clean water at the rate of 5: 1 to form the desired consistency. A slow speed drill is acceptable for mixing. Mix mortar till a unifol consistency is achieved.

APPLICATIONS

Use Notched trowel to apply **POLY TILE MORTAR** on the working area with a thickness of 3-6 mm.

Fix tiles by pressing into place. Ensure that the required joint width is left around each tile. Clean off any surplus on the face of the tiles and between joints before hardening. Leave the tiles for a minimum of 24 hours then grout the joints using **POLY TILE GROUT**.

CLEANING

Tools should be cleaned immediately with water after use .

PACKAGING

POLY TILE MORTAR is supplied in 25kg . packs.

COVERAGE


25 kg **POLY TILE MORTAR** covers 5.50 m² at a thickness of 3 mm.

STORAGE

POLY TILE MORTAR should be stored under shed.

SHELF LIFE

One year when stored as recommended.



HEALTH AND SAFETY

- **POLY TILE MORTAR** is non flammable, any splashes on skin should be washed with water.
- Seek medical assistance, in case of contact with eyes after washing it with plenty of water.

GUARANTEE / WARRANTY

We warrant our products to be of good quality and manufactured to rigid standards. This warranty is in lieu of any and all other warranties expressed or implied.

This data sheet is published for information only. It is believed to be correct but no liability is accepted for it or the suitability of the product for any particular purpose.

POLYCOO services is free and the company dose not accept liability for any loss arising from it.

TECHNICAL SERVICES

For any further technical advice and recommendation for the use of all **POLYCOO** products, please consult the nearest **POLYCOO** technical office.



Under technical collaboration with
Polycoo Industries Ltd.

Sole distributor in Egypt: Polycoo Company

www.polycoo.com

5 Kamel Sedki Street, Ramsis Square, Cairo, Egypt

Sales Tel.: ++202-5918653/++2025918053/++20-122-3102700 Fax: ++202-5918053